

**THERMAL TRANSFER REMOVABLE ADHESIVE
SPEC# 01221**

FACESTOCK

CALIPER - 3mil
DESC. - A bright white, ultra-smooth coated face offering high thermal transfer print quality for medium to high-speed printers. Ideal for barcode printing with or without ink coverage.
TENSILE - **MD** 28# per inch width
CD 16# per inch width
TEAR - **MD** 46grams
CD 50 grams
STIFFNESS – **MD** 82 mg
CD 49 mg

ADHESIVE

TYPE - Emulsion Acrylic
MINIMUM APPLICATION TEMP - +40F
SERVICE TEMP - -65F to +180F
DESC. - A general-purpose removable adhesive with moderate initial tack and minimum adhesion build over time. Excellent long term removability on glass, plastics, metals and corrugate. As these substrates vary in composition, we strongly recommend testing. adhesion to corrugated and superior adhesion to plastics. Complies with FDA 21 CFR 175.105.

LINER

CALIPER - 2.5mil
DESC. - 40# bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance.
TENSILE - **MD** 35# per inch width
CD 16# per inch width
TEAR - **MD** 35 grams
CD 45 grams

SHELF LIFE One year when stored at 72F at 50% RH.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the “Restricted Substances”) are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.