

**TT MATTE SILVER POLYESTER AGGRESSIVE ADHESIVE  
SPEC# 11121**

**FACESTOCK**

**CALIPER** - 2mil  
**DESC.** - A matte silver polyester face featuring excellent tear, heat and chemical resistance. Printable by thermal transfer and flexo. Not recommended for fanfolding.  
**TENSILE** - **MD** 24,000 psi  
**CD** 29,000 psi  
**TEAR** - **N/A**  
**STIFFNESS** - **N/A**

**ADHESIVE**

**TYPE** - Emulsion Acrylic  
**MINIMUM APPLICATION TEMP** - +25F  
**SERVICE TEMP** - -40F to +300F  
**DESC.** - An aggressive adhesive designed to permanently bond to the most demanding surfaces including textured and contoured surfaces, plastics and printed metals.

**LINER**

**CALIPER** - 3.2mil  
**DESC.** - 55# densified kraft premium release liner offers consistent silicone release and good die cutting and dispensing.  
**TENSILE** - **MD**  
**CD**  
**TEAR** - **MD**  
**CD**

**SHELF LIFE** Two years when stored at 72F at 50% RH.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the "Restricted Substances") are not intentionally used in the manufacture of this product and there should be no incidental contamination during their manufacture.