

Thermal Transfer Ribbons for T2N and T4M





RIBBONS DESIGNED FOR USE IN:

- 4" models up to 110mm wide
- SL4M RFID

3040 Saturn Street, Ste. 200 Brea, CA 92821 Tel: 657-258-0816 Fax: 657-258-0817

PrintronixAutoID.com

THERMAL TRANSFER RIBBONS


Supported by a full range of ink formulations, you can be confident that your Genuine Printronix Auto ID ribbon will meet the demands of your label printing application. Enjoy consistent, premium quality and optimized performance through your Printronix Auto ID printer.

The Printronix Auto ID range of thermal transfer ribbons:


OTHER SIZES AVAILABLE UPON REQUEST




8300 - PREMIUM WIDE SPECTRUM WAX




8500 – STANDARD WAX/RESIN




8550 - PREMIUM WAX/RESIN




8600 - SPECIALTY RESIN



8650 – STANDARD RESIN



8770- ULTRA DURABLE RESIN



•	Widely ι	used for	barcode	applications
---	----------	----------	---------	--------------

- Provides excellent print quality
- Suitable for standard labeling applications

 Compatible with most coated and non-coated paper labels 				
Part No.	Width	Length	Rolls/ctn	
257672-008	60mm / 2.36″	450m / 1476 ft	6	
257672-009	83mm / 3.27″	450m / 1476 ft	6	
257672-010	110.0mm / 4.33"	450m / 1476 ft	6	

Resin-enhanced wax

Best scratch and smudge resistance for a wax ribbon

- Supports high speed printing
- · Excellent print quality on all papers and some film materials

Part No.	Width	Length	Rolls/ctn
175391-001	60mm / 2.36″	450m / 1476 ft	6
175391-002	83mm / 3.27″	450m / 1476 ft	6
175391-003	110.0mm / 4.33″	450m / 1476 ft	6

General purpose wax/resin formulation

· Superior print quality on all common papers and films. Our most versatile formulation

Prints at low temperatures and high speed

Part No.	Width	Length	Rolls/ctn
203485-001	60mm / 2.36″	450m / 1476 ft	6
203485-002	83mm / 3.27″	450m / 1476 ft	6
203485-003	110.0mm / 4.33″	450m / 1476 ft	6

· Designed to print on a wide range of coated papers and films

Very sharp print quality, enabling ladder and rotated barcode printing simultaneously

· Enhanced abrasion and scratch resistance

Part No.	Width	Length	Rolls/ctn	
203713-001	60mm / 2.36″	450m / 1476 ft	6	
203713-002	83mm / 3.27″	450m / 1476 ft	6	
203713-003	110.0mm / 4.33″	450m / 1476 ft	6	

· Excellent mechanical resistance, including abrasion and scratch

· Extensive adaptability to a wide range of materials

• Supports higher print speeds

Part No.	Width	Length	Rolls/ctn
203486-001	60mm / 2.36″	450m / 1476 ft	6
203486-002	83mm / 3.27″	450m / 1476 ft	6
203486-003	110.0mm / 4.33″	450m / 1476 ft	6

· Adaptable to a wide range of label materials

Supports high speed printing

Very high resistance to solvents and abrasion

Part No.	Width	Length	Rolls/ctn
204981-001	60mm / 2.36″	450m / 1476 ft	6
204981-002	83mm / 3.27″	450m / 1476 ft	6
204981-003	110.0mm / 4.33″	450m / 1476 ft	6

Developed for extreme environment labeling

Unmatched scratch and solvent resistance

Maximum durability

Part No.	Width	Length	Rolls/ctn
179390-001	60mm / 2.36″	450m / 1476 ft	6
179390-002	83mm / 3.27″	450m / 1476 ft	6
179390-003	110.0mm / 4.33"	450m / 1476 ft	6