

# THERMAL TRANSFER AGGRESSIVE ADHESIVE SPEC# 01301

## FACESTOCK

**CALIPER** - 3.2mil  
**DESC.** - A bright white, ultra-smooth coated face offering high thermal transfer print quality for medium to high-speed printers. Ideal for barcode printing with or without ink coverage.  
**TENSILE** - **MD** 4.5 kg min.  
**CD** 3.5kg min.  
**TEAR** - **MD** 25 grams min.  
**CD** 25 grams min.  
**STIFFNESS** – **MD** 105 mg  
**CD** 65 mg

## ADHESIVE

**TYPE** - Emulsion Acrylic  
**MINIMUM APPLICATION TEMP** - +32F  
**SERVICE TEMP** - -75F to +200F  
**DESC.** - An aggressive high tack permanent with excellent mandrel hold and good adhesion to corrugated, glass, plastic and curved surfaces such as test tubes. "Glove friendly" adhesive.

## LINER

**CALIPER** - 2.5mil  
**DESC.** - 42# bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance.  
**TENSILE** - **MD** 38# per inch width  
**CD** 20# per inch width  
**TEAR** - **MD** 36 grams  
**CD** 41 grams

**SHELF LIFE** One year when stored at 72F at 50% RH.