

THERMAL TRANSFER PIGGYBACK PERMANENT ADHESIVE SPEC# 01801

FACESTOCK

CALIPER - 3.2mil
DESC. - A bright white, ultra-smooth coated face offering high thermal transfer print quality for medium to high-speed printers. Ideal for barcode printing with or without ink coverage.
TENSILE - **MD** 30# per inch width
CD 18# per inch width
TEAR - **MD** 44 grams
CD 50 grams
STIFFNESS – **MD** 105 mg
CD 65 mg

ADHESIVE – SAME ON BOTH PLY'S

TYPE - Emulsion Acrylic
MINIMUM APPLICATION TEMP - +25F
SERVICE TEMP - -65F to +200F
DESC. - A general-purpose permanent adhesive with excellent initial tack, excellent adhesion to corrugated and superior adhesion to plastics. Complies with FDA 175.105 for incidental food contact.

LINER

TOP

CALIPER - 2.5mil
DESC. - 40# bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance.

BOTTOM

CALIPER - 3.2mil
DESC. - 50# bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance.
TENSILE - **MD** 38# per inch width
CD 20# per inch width
TEAR - **MD** 36 grams
CD 41 grams

SHELF LIFE

One year when stored at 72F at 50% RH.