

**50# UNCOATED EDP PERMANENT ADHESIVE
SPEC# 05108**

FACESTOCK

CALIPER - 3.5mil
DESC. - A bright white, uncoated paper with excellent smudge resistance. Suited for impact, dot matrix and continuous laser print technologies.
TENSILE - **MD** 38# per inch width
CD 19# per inch width
TEAR - **MD** 55 grams
CD 60 grams

ADHESIVE

TYPE - Hot Melt Rubber
MINIMUM APPLICATION TEMP - +20F
SERVICE TEMP - -65F to +160F
DESC. - A hot melt rubber permanent adhesive with excellent initial tack, excellent adhesion to corrugated and superior adhesion to plastics. Complies with FDA 21 CFR 175.105.

LINER

CALIPER - 3.2 mil
DESC. - 50# semi-bleached super-calendered kraft liner for die cutting, stripping, and label dispensing. Primarily for roll to roll applications.

SHELF LIFE One year when stored at 72F at 50% RH.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the "Restricted Substances") are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.