

JETLASER PERMANENT SPEC # 09112

Caliper: 6.7 mil
Substance weight: 106 lbs./ream (25" x 38")

Face Paper:

Wood free, machine finished paper, especially designed for ink jet (single and multi-color), laser and photocopiers.
Substance weight: 47 lbs./ream (25" x 38") ISO536
Caliper: 3.5 mil ISO534
Tensile strength: 28 lbf/in (MD) ISO1924
Roughness: 5.0 microns PPS10 ISO8791
Opacity: 90% ISO2471
Brightness: 98% ISO2470

Adhesive:

RP51, strong permanent.
Min. labeling temp: +32F
Min. service temp: -4...+176F
Good uv resistance, good adhesion to non-polar substrates and good low temperature performance. Complies with FDA 21 CFR 175.105.

Liner:

50# White Kraft
Substance weight: 47 lbs./ream (24" X 36")
Caliper: 2.8+/- 0.2 mil

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the "Restricted Substances") are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.