

**TT WHITE POLYESTER AGGRESSIVE ADHESIVE
SPEC# 11122**

FACESTOCK

CALIPER - 2mil
DESC. - A bright white gloss face featuring excellent tear, heat and chemical resistance. Printable by thermal transfer and flexo. Not recommended for fanfolding.
TENSILE - **MD** 24,000 psi
CD 29,000 psi
TEAR - **N/A**
STIFFNESS - **N/A**

ADHESIVE

TYPE - Emulsion Acrylic
MINIMUM APPLICATION TEMP - +25F
SERVICE TEMP - -40F to +300F
DESC. - An aggressive adhesive designed to permanently bond to the most demanding surfaces including textured and contoured surfaces, plastics and printed metals.

LINER

CALIPER - 3.2mil
DESC. - 55# densified kraft premium release liner offers consistent silicone release and good die cutting and dispensing.
TENSILE - **MD**
CD
TEAR - **MD**
CD

SHELF LIFE Two years when stored at 72F at 50% RH.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the "Restricted Substances") are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.