

**TT WHITE POLYESTER PERMANENT ADHESIVE
SPEC# 11191**

FACESTOCK

CALIPER - 2mil
DESC. - A white gloss face featuring excellent tear, heat and chemical resistance. Printable by thermal transfer, flexo and UV letterpress.
TENSILE - **MD** 21,300 psi
CD 28,400psi
TEAR - **N/A**
STIFFNESS – **N/A**

ADHESIVE

TYPE - Emulsion Acrylic
MINIMUM APPLICATION TEMP - +50F
SERVICE TEMP - -40F to +302F
DESC. - A general purpose permanent adhesive with medium initial tack, ultimate adhesion to a wide variety of substrates, and low adhesive ooze.
Complies with FDA 21 CFR 175.105.

LINER

CALIPER - 3.2mil
DESC. - 50# bleached, super-calendered paper. Promotes very good die-cutting and matrix stripping characteristics.
TENSILE - **MD** 48# per inch width
CD 26# per inch width
TEAR - **MD** 51.1 grams
CD 59.6 grams

SHELF LIFE One year when stored at 72F at 50% RH.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the “Restricted Substances”) are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.