



## 2.6MIL WHITE TT POLYPROPYLENE/ PERMANENT ADHESIVE SPEC# 12135

### FACESTOCK

**CALIPER** - 2.6mil  
**DESC.** - A white gloss corona-treated biaxially oriented film for rigid containers where durability is needed. Good conformability and may work for squeezable containers. Limited outdoor and UV resistance. Printable by thermal transfer and flexo.  
**TENSILE** - **MD** 28,000 psi  
**CD** 15,000 psi  
**TEAR** - N/A  
**STIFFNESS** – **MD** 21 mg

### ADHESIVE

**TYPE** - Emulsion Acrylic  
**MINIMUM APPLICATION TEMP** - +25F  
**SERVICE TEMP** - -75F to +200F  
**DESC.** - A general-purpose permanent acrylic emulsion with aggressive initial tack, excellent ultimate adhesion and mandrel hold. Very good adhesion to corrugated, glass, and various plastic substrates. Also used in healthcare applications and considered to be latex glove friendly. Complies with FDA 21 CFR 175.105.

### LINER

**CALIPER** - 2.5mil  
**DESC.** - Semi-bleached super-calendared kraft paper.  
**Basis Weight, lbs-** 40# (24" x 36"/500 sheets)

### SHELF LIFE

One year when stored at 72° F and 50% R.H.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the "Restricted Substances") are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.