

**3MIL MATTE SYNTHETIC TT / PERMANENT ADHESIVE
SPEC# 12136**

FACESTOCK

CALIPER - 3.0mil
DESC. - A bright white biaxial-oriented polypropylene film with strong durability and high moisture resistant characteristic. This top coated film is excellent for printing via thermal transfer and flexo.
TENSILE, kg min- **MD 9**
CD 16
TEAR, kg min **MD 24**
CD 33
BASIS WT, lbs. - 42.5# (24X36/500)
OPACITY - 80%

ADHESIVE

TYPE - Emulsion Acrylic
MINIMUM APPLICATION TEMP - +25F
SERVICE TEMP - -75F to +200F
DESC. - A general-purpose permanent acrylic emulsion with aggressive initial tack, excellent ultimate adhesion and mandrel hold. Very good adhesion to corrugated, glass, and various plastic substrates. Also used in healthcare applications and considered to be latex glove friendly. Complies with FDA 21 CFR 175.105.

LINER

CALIPER - 2.5mil
DESC. - Semi-bleached super-calendared kraft paper.
Basis Weight, lbs- 40# (24" x 36"/500 sheets)

Shelf Life: One year when stored at 72° F and 50% R.H.

The product listed above meets the requirements specified by the **European Union Directive 2002/95/EC(RoHS)** to eliminate the use of **lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated diphenyl ethers**. These chemicals (collectively referred to as the "Restricted Substances") are not intentionally used in the manufacture of DLS products and there should be no incidental contamination during their manufacture.

