

**TT POLYOLEFIN PERMANENT ADHESIVE
SPEC# 13100**

FACESTOCK

CALIPER - 4.0mil
DESC. - A semi-gloss white film with excellent receptivity to a variety of thermal transfer ribbon and printer combinations. Face is resistant to water, mild acids, bases, salts, most petroleum-based oils, greases and aliphatic solvents.
TENSILE - **MD** 250,000 psi
CD 90,000 psi
TEAR - **N/A**
STIFFNESS - **N/A**

ADHESIVE

TYPE - Emulsion Acrylic
MINIMUM APPLICATION TEMP - +10F
SERVICE TEMP - -40F to +176F
DESC. - A clear permanent adhesive offering high initial tack and cold temperature properties when applied to most packaging films. Features good UV resistance for outdoor use for approximately 6 months.
Complies with FDA 21 CFR 175.105.
Passed British Standard 5609 (BS 5609:1986) Section 2 testing for International Maritime Dangerous Goods (IMDG) certification.

LINER

CALIPER - 3.2mil
DESC. - 50# bleached super-calendered paper stock with good back printability. Good for roll or fanfold applications.
TENSILE - **MD** 38# per inch width
CD 18# per inch width
TEAR - **MD** 38 grams
CD 47 grams

SHELF LIFE One year when stored at 72F at 50% RH.